

15B MAX

New Model



VICTOR 15B 17B MAX NEW Full Function Digital Multimeter 1000V fuse True RMS Multimeter

Technical data

Model		15B MAX	17B MAX
Basic Function	Range	Accuracy	
DCV	600mV	±(1.0%+10)	
	6V/60V/600V/1000V	±(0.5%+3)	
ACV	600mV	±(3.0%+3)	
	6V/60V/600V/1000V	±(1.0%+3)	
DCA	600uA/6000uA/60mA/500mA/6A/10A	±(1.5%+3)	
ACA	600uA/6000uA	±(1.2%+8)	
	60mA/500mA	±(1.5%+8)	
Resistance	6A/10A	±(2.0%+8)	
	600Ω/6kΩ/60kΩ/600kΩ/6MΩ	±(0.5%+3)	
	60MΩ	±(2.0%+5)	
Capacitance	6nF	±(5.0%+10)	
	60nF/600nF	±(2.0%+5)	
	6uF/60uF/600uF/6mF	±(5.0%+5)	
Frequency	10Hz~10MHz	±(0.1%+3)	
Duty cycle	1%~99%	±(1.0%+4)	
Temperature	(-55~1000)°C/(-67~1832)°F	/	±(1.5%+15)
Special Functions			
Display	LCD display		
Max display	5999 (3 5/6) digit and unit display		
Conversion rate	3 times per second		
Over range	The highest position displays "OL"		
Low voltage	The battery symbol appears		
T-RMS	√		
Diode	√		
on/offbuzzing	√		
Max/min	√		
One click wake-up	√		
Sound and light alarm	Sound and light alarm for incorrect operation of current mode		
Data retention	√		
Backlight display	√		
Relative value	√		
Automatic shutdown	√		
work environment	(0-40) °C, relative humidity<75%		
Storeay environment	-10-50°C, relative humidity<85%		
Power Supply	1.5V * 2 AA batteries		
size	187x88x45mm		
weight	About 427g		

17B MAX

New Model

