

925



Technical data

Model	925	
Basic Function	Range	Accuracy
DC Voltage	10V/100V	$\pm(0.5\%+3)$
	600V	$\pm(1.0\%+10)$
AC Voltage	10V/100V	$\pm(0.8\%+5)$
	600V	$\pm(1.2\%+10)$
DC Current	60mA	$\pm(1.0\%+5)$
	600mA	$\pm(1.5\%+10)$
AC Current	60mA	$\pm(1.5\%+10)$
	600mA	$\pm(2.0\%+5)$
Capacitance	100nF/1000nF	$\pm(4.0\%+20)$
	10uF/100uF/1000uF/1mF	$\pm(3.5\%+20)$
	10mF/100mF	$\pm(10\%+10)$
Frequency	10Hz~1MHz	$\pm(0.1\%+5)$
Resistance	1000Ω	$\pm(1.3\%+5)$
	10kΩ/100kΩ/1MΩ	$\pm(0.8\%+3)$
	10MΩ	$\pm(1.5\%+3)$
	20MΩ	$\pm(2.0\%+10)$
Special Function		
High battery indication	√	
Auto power off	√	
Diode	√	
Display	LCD displaying	
Over range indication	MSD displays "OL"	
Max. Display	9999	
Size	137×70×20 mm	
Weight	approx.133g	
Power	built-in 3.7V 500mA lithium battery	
Operating environment	Temperature (0 - 40)°C,humidity<75%RH	
Storage environment	Temperature (-20 - 60)°C,humidity<85%RH	