



60F/60G/60H

Technical data

Function		60F	60G	60H
Insulation resistance	Resistance range	50V /200MΩ	N/A	N/A
		100V / 500MΩ	N/A	100V / 200MΩ
		250V / 2000MΩ	250V /2000M	250V / 500MΩ
		500V /5GΩ	500V /5GΩ	500V /1GΩ
		1000V /10GΩ	1000V /10GΩ	1000V /20GΩ
		1500V /20GΩ	N/A	N/A
		2000V /50GΩ	N/A	N/A
		2500V /100GΩ	2500V /50GΩ	N/A
Voltage test	DC Range	0 ~ 1000V	30 ~ 1000V	0 ~ 1000V
	AC Range	30 ~ 750V	30 ~ 750V	30 ~ 750V
PI		✓	✓	✓
DAR		✓	✓	✓
COMP		✓	✓	✓
Short circuit current		About 1.3mA	About 1.3mA	About 1.3mA
TIME		✓	✓	✓
Automatic release voltage		✓	✓	✓
Power Supply		Alkaline battery1.5V (LR6) ×The 8 section	Alkaline battery1.5V (LR6) ×The 8 section	Alkaline battery1.5V (LR6) ×The 8 section
Automatic shutdown		✓	✓	✓
Backlight		The white LED	The white LED	The white LED
Storage		100 groups	100 groups	100 groups
adapter interface		✓	✓	✓
Size		178(L)×110(W)×59(D)mm	178(L)×110(W)×59(D)mm	178(L)×110(W)×59(D)mm
Weight		About600g(Does not contain a battery)	About600g(Does not contain a battery)	About600g(Does not contain a battery)
Standard Quantity Per Carton		12 pcs	12 pcs	12 pcs
Standard Carton Measurement		430×350×225mm	430×350×225mm	430×350×225mm
Standard Carton Gross Weight		12.4KG	12.2KG	10.8KG