

923E

New Model



VICTOR 923E Intelligent Large Screen Digital Multimeter with VA color screen 5999 bit display

Technical data

| Basic Function | 923E | Accuracy |
|------------------------------|--|-------------------------------------|
| DC voltage | 600mV/6V/60V/600V | ±(0.5%+3) |
| AC voltage | 6V/60V/600V | ±(1.0%+3) |
| DC current | 600mA/6A/10A | ±(1.2%+3) |
| AC current | 600mA/6A/10A | ±(1.2%+3) |
| Resistance | 600Ω/6kΩ/60kΩ/600kΩ/6MΩ 60MΩ | ±(1.0%+5) ±(2.0%+10) |
| Capacitance | 6nF/60nF/600nF/6uF/60uF/600uF 6mF 60mF | ±(4.0%+5) ±(5.0%+5) ±(10%+10) |
| Frequency | 6Hz/60Hz/600Hz/6kHz/60kHz/600kHz/6MHz/10MHz | ±(1.0%+3) |
| Temperature | (-40~1000)°C or (-40~1832)°F | ±3°C or ±6°F |
| Essential information | | |
| LCD display | 5999 max | |
| Overload | OL | |
| Alarm signal | Audible and visual alarm | |
| Power | 1.5V AAA*4 | |
| Low voltage | √ | |
| Auto shutdown | No operation for 15 minutes | |
| Size | 144*73*27mm | |
| Weight | About 235g | |
| Work environment | 0~40°C(<75%RH) | |
| Storage | -20~60°C(<85%RH) | |
| Jack prompt | √ | |
| NCV | √ | |
| Flashlight | √ | |
| Data retentio | √ | |
| Diode | √ | |
| On off buzzer | √ | |

925



Technical data

| Model | 925 | |
|----------------|-----------------------|------------|
| Basic Function | Range | Accuracy |
| DC Voltage | 10V/100V | ±(0.5%+3) |
| | 600V | ±(1.0%+10) |
| AC Voltage | 10V/100V | ±(0.8%+5) |
| | 600V | ±(1.2%+10) |
| DC Current | 60mA | ±(1.0%+5) |
| | 600mA | ±(1.5%+10) |
| AC Current | 60mA | ±(1.5%+10) |
| | 600mA | ±(2.0%+5) |
| Capacitance | 100nF/1000nF | ±(4.0%+20) |
| | 10uF/100uF/1000uF/1mF | ±(3.5%+20) |
| | 10mF/100mF | ±(10%±10) |
| Frequency | 10Hz~1MHz | ±(0.1%±5) |
| Resistance | 1000Ω | ±(1.3%+5) |
| | 10kΩ/100kΩ/1MΩ | ±(0.8%±3) |
| | 10MΩ | ±(1.5%+3) |
| | 20MΩ | ±(2.0%±10) |

| Special Function | |
|-------------------------|--|
| High battery indication | √ |
| Auto power off | √ |
| Diode | √ |
| Display | LCD displaying |
| Over range indication | MSD displays "OL" |
| Max. Display | 9999 |
| Size | 137*70*20 mm |
| Weight | approx.133g |
| Power | built-in 3.7V 500mA lithium battery |
| Operating environment | Temperature (0 - 40)°C, humidity<75%RH |
| Storage environment | Temperature (-20 - 60)°C, humidity<85%RH |