

Insulation Tester

Specifications	60B+		
Measuring Voltage	250V+10%	500V+10%	1 000V+10%
Range	0.4MΩ~999 MΩ	0.6MΩ~1999 MΩ	0.8MΩ~4999 MΩ
Current of Short Circuit	1.8mA	1.8mA	1.6mA
Median Resistance	2MΩ	2MΩ	5MΩ
Jack Position	L/E		
Features			
Low Battery Indication	√		
Backlight display	√		
Alarm Function	Red indicator light is iluminated		
Over Load Indication	√		
Unit Symbol Display	√		
Auto Power Off	√		
Max. Display	4999		
Using Temperature	(0~40)°C		
Relative Humidity	30%RH~85%RH		
Input Impedance	1MΩ		
Frequency Response	(50-200) Hz		
Over Range Display	"1"		
General Information			
Power Color	Case: black, Holster color : orange		
Power Supply	9V (8x1 .5V AA); AC adapter (not included)		

New Model DC 1500V



60B+

Specifications	60D+		
Measuring Voltage	500V	1000V	2500V
Measurement range	0.6MΩ~4.99GΩ	1MΩ~9.99GΩ	3MΩ~49.9GΩ
Open-circuit voltage	DC 500V+20% -0%	DC 1000V+20% -0%	DC 2500V+20% -0%
Rated test current	500kΩ Load≥1.0mA	1MΩ Load≥1.0mA	2.5MΩ Load≥1.0mA
Accuracy	±(5%+5)	±(5%+5)	≥3MΩ±(5%+5)
Features			
Low Battery Indication	√		
Backlight display	√		
Alarm Function	Red indicator light is illuminated		
Over Load Indication	√		
Unit Symbol Display	√		
Auto Power Off	√		
Max. Display	1999		
Using Temperature	(0~40)°C		
Relative Humidity	30%RH~85%RH		
Input Impedance	1MΩ		
Frequency Response	(50-200) Hz		
Over Range Display	"1"		
General Information			
Power Color	Case: black, Holster color : orange		
Power Supply	9V (8x1 .5V AA); AC adapter (not included)		



60D+