



606+



606A+



606B+



606C+

FUNCTION	606+	606A+	606B+	606C+	Accuracy
DCV	200mV/2V/20V	600mV/6V/60V	600mV/6V/60V	600mV/6V/60V	± (0.5%+7)
	200V	600V	600V	600V	± (1.0%+ 20)
	600V	/	/	/	± (1.2%+ 20)
ACV	2V/20V	6V/60V	6V/60V	6V/60V	± (0.8%+ 10)
	200V	600V	600V	600V	± (1.2%+ 25)
	600V	/	/	/	± (1.5%+25)
LOW IMPEDANCE ACV	2V/20V	6V/60V	6V/60V	6V/60V	± (0.8%+ 10)
	200V	300V	300V	/	± (1.2%+25)
	300V	/	/	/	± (1.5%+ 25)
ACA	/	/	/	300V	± (1.0%+12)
	2A	6A	6A	/	± (4.0%+ 50)
	20A	60A	60A	/	± (4.0%+ 35)
DCA	200A/600A	600A	600A	/	± (4.0%+15)
	/	/	/	60A/600A	± (4.0%+10)
	/	/	/	60A/600A	± (4.0%+10)
RESISTANCE	200Ω/2kΩ/20kΩ	600Ω/6kΩ/60kΩ	600Ω/6kΩ/60kΩ	600Ω/6kΩ/60kΩ	± (1.0%+ 5)
	/200kΩ/2MΩ	/600kΩ/6MΩ	/600kΩ/6MΩ	/600kΩ/6MΩ	± (1.5%+15)
	20MΩ	20MΩ	20MΩ	20MΩ	± (1.5%+15)
CAPACITANCE	/	6nF	6nF	6nF	± (5.0%+40)
	/	60nF/600nF/6uF	60nF/600nF/6uF	60nF/600nF/6uF	± (5.0%+ 10)
	/	60uF/600uF/6mF	60uF/600uF/6mF	60uF/600uF/6mF	± (5.0%+ 10)
FREQUENCY	/	10Hz/100Hz/1kHz/10kHz/100kHz/1MHz/10MHz	10Hz/100Hz/1kHz/10kHz/100kHz/1MHz/10MHz	10Hz/100Hz/1kHz/10kHz/100kHz/1MHz/10MHz	± (0.3%+3)
	/	/	-20°C~1000°C (-4~1832)°F	-20°C~1000°C (-4~1832)°F	/
	/	/	/	/	/

Display method	LCD display 5999 count	Max/Min	√
Maximum display	5999 count (606+ 1999count)	Low Z	√
Diode measurement	√	Working temperature and humidity	(0~40)°C <75%
Data retention	√	Storage temperature and humidity	(-10~50)°C <80%
NCV measurement	√	Automatic shut-down	About 15 minutes
Fire detection	√	Over-range display	the highest digit displays OL
Low voltage warning	√	Unit symbol	√
Flashlight lighting	√	Open jaws	35mm
True effective value	√	input resistance	10MΩ
INRUSH	606C+ only	Sampling rate	3 times/sec
VFC	606C+ only	power supply	Two AAA batteries