



890H+

890G+

TRUE RMS

Technical data

Basic function	Range	Accuracy VICTOR 890H+	Accuracy VICTOR 890G+
DCV	600mV/6V/60V/600V/1000V	±(0.5%+3)	±(0.5%+3)
ACV	600mV/6V/60V/600V/750V	±(0.8%+5)	
ACV	6V/60V/600V/750V		±(0.8%+5)
DCA	600μA/6000μA/60mA/600mA/10A	±(1.2%+3)	
DCA	60μA/60mA/600mA/10A		±(1.2%+3)
ACA	600μA/6000μA/60mA/600mA/10A	±(1.5%+3)	
	60mA/600mA/10A		±(1.5%+3)
Resistance	600Ω/6kΩ/60kΩ/600kΩ	±(1.0%+3)	±(1.0%+3)
	6MΩ/60MΩ	±(1.5%+3)	±(1.5%+3)
Capacitance	10nF/100nF/1000nF/10μF/100μF/1000μF	±(4%+5)	±(4%+5)
	10mF/100mF	±(5%+5)	±(5%+5)
Frequency/duty cycle	10Hz/100Hz/1000Hz/10kHz/100kHz/1000kHz	±(1.0%+3)	±(1.0%+3)
	10MHz/1~99%	±(3.0%+3)	±(3.0%+3)
Special function		890H+	890G+
Temperature	-20°C~1000°C - 4°F ~ 1832°F	✓	
NCV test		✓	✓
Live wire test		✓	✓
Battery test		✓	✓
Input terminal prompt		✓	✓
High voltage prompt		✓	✓
Diode test		✓	✓
Continuity alarm		✓	✓
Low battery		✓	✓
Backlight		✓	✓
Flashlight		✓	✓
Auto power off		✓	✓
Function protection		✓	✓
shakeproof protection		✓	✓
Input impedance		10MΩ	10MΩ
ACV frequency response		10Hz ~ 1kHz	10Hz ~ 1kHz
Operation method		auto range	auto range
Display		6000 counts	6000 counts
Supply		Battery 2*1.5V AA	Battery 2*1.5V AA